

Harvest the Sunshine

JA SOLAR

465W




Hail Resistance Class 4

JAM54D40 LB

Black Frame
n-type Double Glass Bifacial Modules

Premium Cells



MBB Half-Cell
Technology

26%



Cell Conversion
Efficiency

Premium Modules



Higher power
generation better LCOE




n-type with very
Lower LID



Better Temperature
Coefficient



Better low irradiance
response





25-year product
warranty



30-year linear power
output warranty

Comprehensive Certificates


- IEC 61215, IEC 61730, UL 61215, UL 61730
- ISO 9001: 2015 Quality management systems
- ISO 14001: 2015 Environmental management systems
- ISO 45001: 2018 Occupational health and safety management systems
- IEC 62941: 2019 Terrestrial photovoltaic (PV) modules - Quality system for PV module manufacturing



DEEP BLUE 4.0 Pro

JAM54D40 LB

n-type Double Glass Bifacial Modules



MECHANICAL PARAMETERS

Cell	Mono
Weight	28kg
Dimensions	1762±2mm×1134±2mm×30±1mm
Cable Cross Section Size	4mm²(IEC), 12 AWG(UL)
No. of cells	108(6×18)
Junction Box	IP68, 3diodes
Connector	QC 4.10-351/ MC4-EVO2A
Cable Length (Including Connector)	Portrait: 400mm(+)/200mm(-) Landscape: 1200mm(+)/1200mm(-)
Front Glass/Back Glass	2.8mm/2.0mm
Packaging Configuration	36pcs/Pallet, 792pcs/40HQ Container

Remark: customized frame color and cable length available upon request

ELECTRICAL PARAMETERS AT STC


TYPE	JAM54D40 -440/LB	JAM54D40 -445/LB	JAM54D40 -450/LB	JAM54D40 -455/LB	JAM54D40 -460/LB	JAM54D40 -465/LB
Rated Maximum Power(P _{max}) [W]	440	445	450	455	460	465
Open Circuit Voltage (V _{oc}) [V]	38.90	39.10	39.30	39.50	39.70	40.20
Maximum Power Voltage(V _{mp}) [V]	32.47	32.65	32.82	33.00	33.17	33.50
Short Circuit Current(I _{sc}) [A]	14.31	14.40	14.48	14.56	14.64	14.65
Maximum Power Current(I _{mp}) [A]	13.55	13.63	13.71	13.79	13.87	13.88
Module Efficiency [%]	22.0	22.3	22.5	22.8	23.0	23.3
Power Tolerance	0~+3%					
Temperature Coefficient of I _{sc} (α _{Isc})	+0.045%/°C					
Temperature Coefficient of V _{oc} (β _{Voc})	-0.250%/°C					
Temperature Coefficient of P _{max} (γ _{Pmp})	-0.290%/°C					
STC	Irradiance 1000W/m², cell temperature 25°C, AM1.5G					

Remark: Electrical data in this catalog do not refer to a single module and they are not part of the offer. They only serve for comparison among different module types.

ELECTRICAL CHARACTERISTICS WITH 10% SOLAR IRRADIATION RATIO

TYPE	JAM54D40 -440/LB	JAM54D40 -445/LB	JAM54D40 -450/LB	JAM54D40 -455/LB	JAM54D40 -460/LB	JAM54D40 -465/LB
Rated Max Power(P _{max}) [W]	475	481	486	491	497	502
Open Circuit Voltage(V _{oc}) [V]	38.90	39.10	39.30	39.50	39.70	40.20
Max Power Voltage(V _{mp}) [V]	32.47	32.65	32.82	32.99	33.17	33.50
Short Circuit Current(I _{sc}) [A]	15.46	15.55	15.64	15.73	15.81	15.82
Max Power Current(I _{mp}) [A]	14.63	14.72	14.81	14.89	14.98	14.99
Irradiation Ratio (rear/front)	10%					

CHARACTERISTICS



OPERATING CONDITIONS

Maximum System Voltage	1500V DC
Operating Temperature	-40°C~+85°C
Maximum Series Fuse Rating	30A
Maximum Static Load, Front	8000Pa(167 lb/ft²)
Maximum Static Load, Back	5000Pa(104 lb/ft²)
Hail Class	Hail Resistance Class 4(HW4)
NOCT	45±2°C
Bifaciality	80%±5%
Safety Class	Class II
Fire Performance	Class C