



DECLARATION OF CONFORMITY N. 26-018-B

Issued by: **SUPSI - PV LAB - SAS** accredited laboratory ISO 17025 n. 0531

Based on the test report: n. 24-116/A-REP2-rev2_ed0 dated 2026.03.13

Issued by: **SUPSI - PV LAB** Via Flora Ruchat-Roncati, 15 -CH 6850 Mendrisio – Switzerland

We declare that the building component: glass/glass photovoltaic module, mod.

Soli tek cells, UAB- Model/Type: SOLID SOLRIF D (framed versions)

| TestedPV Module Type | n.cells | Cell technology | Front glass / superstrate | Rear glass / back-strate | Module size (gross) | Power [W] |
|----------------------------------|---------|---|--|--|---------------------|-----------|
| SOLID Solrif D B.108 435W | 108 | Mono-crystalline Si TOPCon, half-cut, bi-facial | Partially toughened (Heat strengthened, low iron, patterned with ARC) GLASS thickness 3.2 mm | Partially toughened (Heat strengthened) GLASS thickness 3.2 mm | 1722 x 1134 x 35 mm | 435 |

Extended by similarity, without re-testing to:

| | n.cells | Cell technology | Front glass / superstrate | Rear glass / back-strate | Module sizes (gross) | Max Power [W] |
|---------------------------------|---------|---|--|--|----------------------|---------------|
| SOLRIF D Agro B.64 | 64 | Mono-crystalline Si TOPCon, half-cut, bi-facial | Heat strengthened, low iron, patterned with ARC GLASS thickness 3.2 mm | Partially toughened (heat strengthened) GLASS thickness 3.2 mm | 1806x1160x20 mm | 300 |
| SOLRIF D Black B.96 | | | Heat strengthened, low iron, black painted patterned with ARC GLASS thickness 3.2 mm | | | 455 |
| SOLRIF D Satin B.96 | 96 | Mono-crystalline Si TOPCon, half-cut, bi-facial | Heat strengthened, low iron, etched GLASS, thickness 3.2 mm | Partially toughened (heat strengthened) GLASS thickness 3.2 mm | | 445 |
| SOLRIF D Semi-clear B.96 | | | Heat strengthened, low iron, patterned with ARC GLASS thickness 3.2 mm | | | 455 |
| SOLRIF D Terracotta Bronze B.96 | | | Heat strengthened, low iron, coloured patterned with ARC GLASS thickness 3.2 mm | | | 370 |
| SOLRIF D Terracotta Orange B.96 | | | Heat strengthened, low iron, coloured patterned with ARC GLASS thickness 3.2 mm | | | 300 |

| | |
|------------------|--|
| Manufactured by: | Soli tek cells, UAB - Mokslininkų g. 6A 08412 Vilnius Lithuania |
| License holder: | Soli tek cells, UAB - Mokslininkų g. 6A 08412 Vilnius Lithuania |

has been tested according to:

HAIL RESISTANCE CLASS HW 5

(According to VKF - Prüfbestimmung Nr. 25 - Photovoltaik Module - ver. 1.03)

Disclaimer: the relevant technical data, materials, components descriptions and mounting methods are listed in the test report. SUPSI PVLab does not assume responsibility for the liability of any information, data and specifications provided by the applicant. Any changes of the design, materials, components, processing or mounting methods may require the repetition of testing.

Mendrisio, 2026.03.13

Giovanni Bellenda
 Head of SUPSI PVLab

Mauro Cacciavo
 Head of SUPSI PV sector