

# **Certificate of compliance**

Applicant: GoodWe Technologies Co., Ltd

No. 96 Guantai Road (Houjie Section) Houjie Town Dongguan City Guangdong Province 523942

People's Republic of China

Product: Photovoltaic (PV) inverter

Model: GW25K-MT,

GW30K-MT, GW36K-MT

The device is designed to work as a generation unit of the type: A and B\*

Inverter for three-phase parallel connection to the public grid. The network monitoring and disconnection device is an integral part of the above-mentioned model.

#### Applied rules and standards:

#### EN 50549-1:2019/A1:2023

Requirements for parallel connection of installations with distribution networks - Part 1: Connection to an LV distribution network - Production of installations up to and including Type B

- 4.4 Normal operating range
- 4.5 Immunity to disturbances\*
- 4.6 Active response to frequency deviation
- 4.7 Power response to voltage variations and voltage changes
- 4.8 EMC and power quality
- 4.9 Interface protection
- 4.10 Connection and starting to generate electrical power
- 4.11 Ceasing and reduction of active power on set point
- 4.12 Remote information exchange
- 4.13 Requirements regarding single fault tolerance of interface protection system and interface switch

#### EN 50549-10:2022

Requirements for generating plants to be connected in parallel with distribution networks - Part 10: Tests for conformity assessment of generating units

#### Commission Regulation (EU) 2016/631 of 14 April 2016

Establishing a network code on requirements for grid connection of generators (NC RFG).

Type approval for generation units to use in Type A and B\* plants.

\* 4.5 Immunity to disturbances, only limited grid support mode was tested (zero current mode) for FRT function.

At the time of issue of this certificate, the safety concept of an aforementioned representative product corresponds to the valid safety specifications for the specified use in accordance with regulations.

Domenik Kol

Head of Energy Systems Germany

Report number: PV2307WDG0008-1

Certificate number: U25-0183

Certification Program: NSOP-0032-DEU-ZE-V10
Date of issue: 2025-03-04
Accreditation



Accredited certification body by Deutsche Akkreditierungsstelle GmbH (DAkkS) according to ISO/IEC 17065. The accreditation is valid only for the scope listed in the annex of the accreditation certificate D-ZE-12024-01-00. The Deutsche Akkreditierungsstelle GmbH (DAkkS) is signatory of the multilateral arrangements of EA, ILAC and IAF for mutual recognition.

Without the written consent of Bureau Veritas Consumer Products Services Germany GmbH excerpts of this certificate of conformity shall not be reproduced



## Annex certificate of conformity No. U25-0183

Extract from test report PV2307WDG0008-1 issued by a testing laboratory accredited by "A2LA" according to ISO/IEC 17025. The accreditation is only valid for the scope listed in the annex of the accreditation certificate "2951.01".

Manufacturer	GoodWe Technologies Co., Ltd No. 96 Guantai Road (Houjie Section) Houjie Town Dongguan City Guangdong Province 523942 People's Republic of China				
Product type	Photovoltaic (PV) inv	erter			
Ctatia converter model	GW25K-MT	CW30K MT	GW36K-MT		
Static converter model	GVVZ3N-IVI I	GW30K-MT	GVV30K-IVI I		
Input DC (photovoltaic)  MPP voltage range [V]	200-950	200-950	200-950		
Max. input voltage [V]	1100	1100	1100		
Max. input current per MPPT [A]	30 / 30 /30	30 / 30 /30	30 / 30 /30		
Output AC	30730730	30730730	30 / 30 /30		
Rated AC voltage [V]	230, 3L/N/PE, 50Hz	230, 3L/N/PE, 50Hz	230, 3L/N/PE, 50Hz		
Max. output current [A]	40.0	48.0	53,3		
Nom. converter output (P <sub>NINV</sub> ) [kW]	25,0	30,0	36,0		
Rated apparent power [kVA]	25,0	30,0	36,0		
and the same of th					
Interface protection system and ir	nterface switch (Netwo	rk and system protect	ion "NS-protection")		
Type of protection	Integrated NS-prote	Integrated NS-protection			
Assigned to generation unit type	d to generation unit type GW25K-MT, GW30K-MT, GW36K-MT				
Integrated interface switch	Type of switching equipment 1: Relay (Model HF176F) Type of switching equipment 2: Relay (Model HF176F)				
	Note: The output is switched off by the inverter bridge and two relay in series in each line and neutral.				

### Note

The settings of the interface protection are password protected adjustable.

In case the above stated generators are used with an external protection device, the protection settings of the inverters are to be adjusted according to the manufacturer's declaration.

The above stated generators are tested according to the requirements in the EN 50549-1:2019 Commission Regulation (EU) 2016/631 of 14 April 2016. Any modification that affects the stated tests must be named by the manufacturer/supplier of the product to ensure that the product meets all requirements.