

CERTIFICATE n. 22-024-A

Issued by: **SUPSI - PV LAB**
SAS accredited laboratory ISO 17025 n. 0531

Based on the test report: n. 22-024/A-REP1-rev1 dated 22.06.2022

Issued by: SUPSI – PV LAB
Campus Mendrisio, CH - 6850 Mendrisio - Switzerland

We declare that the building component: photovoltaic module with integrated frame and associated mounting system, mod.

ARRES 3.0 - PREMIUM L

PV Module Type	Cells n.	Cell technology	Glass / superstrate	Module size (gross)	Power [W]
SOLUXTEC PSMXSC400	108	monocrystalline Si- half-cut	tempered solar glass - thickness 4 mm	1748 x 1188 x 20 mm	400

extended for similarity, without retesting to:

Type	Cells n.	Cell technology	Glass / superstrate	Module size	Power [W]
SOLUXTEC PSMXSC405	108	monocrystalline Si – half-cut	tempered solar glass - thickness 4 mm	1748 x 1188 x 20 mm	405
SOLUXTEC PSMXSC410	108	monocrystalline Si- half-cut	tempered solar glass - thickness 4 mm	1748 x 1188 x 20 mm	410
SOLUXTEC PSMXSC415	108	monocrystalline Si- half-cut	tempered solar glass - thickness 4 mm	1748 x 1188 x 20 mm	415

Manufactured by:	Solarmarkt GmbH - Neumattstrasse 2 - CH-5000 Aarau - Switzerland
License holder:	Solarmarkt GmbH - Neumattstrasse 2 - CH-5000 Aarau - Switzerland

has been tested according to:

HAIL RESISTANCE CLASS HW5

(according to VKF - Prüfbestimmung Nr. 25 - Photovoltaik Module - ver. 1.03)

Technical data, materials and components description are listed in the report. Any changes of the design, materials, components or processing may require the repetition of testing.

Mendrisio, 22.06.2022

Giovanni Bellenda
Lab. Technical Responsible

Mauro Caccivio
Head of SUPSI PVLab